## **HWOF** Series

## Standard features include:

- Compact design with steerable pull handle for maximum portability.
- Stainless steel tanks, skirt and vent withstand years of use and will not rust.
- Triplex ceramic plunger pumps are belt driven at slower speed for reduced wear when compared to direct drive pumps.
- High pressure soap provides superior cleaning compared with soap injector systems.
- · Stainless steel fuel, water, and detergent tanks.
- Metering valve allows exact setting for desired soap concentration.
- Pressures up to 3000 PSI and volumes up to 5 GPM.
- Available with TEFC 1750 RPM Baldor or Leeson electric motors, or Honda GX series gas engines with built-in 2:1 gear reduction.
- Electronic temperature sensor for precise temperature control.
- Industrial Beckett oil burner provides efficient trouble-free operation.
- · Flame safeguard controls are standard.
- · Heavy duty pump & motor switch.
- Pneumatic wheels provide easy movement over any surface, unlike solid or semi-pneumatic wheels.
- Safety relief valve, pressure gauge, and prime valve are all standard items.
- Supplied with 50 feet of wire braid high pressure hose, quick couplers, easy open trigger gun, high pressure swivel, 36" or 48" insulated wand & stainless steel nozzle.
- · Optional stainless steel hose reel.



Model HWOFPX20-4-20-G shown with optional hose reel







